

Weatherization and Insulation - ACRYLIC LATEX CAULK WITH SILICONE

DAP Power Point 200 Acrylic Latex Caulk with Silicone is a versatile, durable caulk that provides a waterproof seal for any project. It's paintable in 30 minutes and won't discolor paint, making it ideal for professional results. Plus, it's easy to apply, low in odor, and cleans up with water.

PRODUCT SPECIFICATIONS

Appearance/Consistency	Gunnable, non-sag paste
Base Polymer	Siliconized acrylic polymer
Filler	Calcium carbonate
Volatile	Water
Weight % Solids	53
Application Temp. Range	40°F to 100°F
Tooling Time (Working Time)	60 minutes
Tack Free Time	60 minutes
Full Dry Through	7-14 days
Color	White
Unit Size	10.1 fl oz (300 mL)
Standards	Exceeds ASTM C834 requirement



FEATURES

- Paintable in 30 minutes
- Easy water clean up
- Exceeds ASTM C834
- 40 Year guarantee
- Interior/exterior use
- Low odor

USES

Window frames, Door frames, Baseboards, Moldings, Trims, Corner joints, Pipes, Vents, Siding, Gaps & Cracks.

MODEL INFORMATION

MODEL NUMBER	CASE QTY
WX/TUBECAULK/1	12

1-877-255-0004 | info@greenliteusa.com
www.greenliteusa.com

V1 - 20250123

