



## Electrification - SMART EV HOME CHARGING STATION

Power your EV with the Greenlite Smart Level 2 Charger, a robust and reliable solution engineered for Canadian climates. This WiFi-enabled charger delivers up to 10kW of power with adjustable current output (40A or 32A) and works seamlessly with any OCPP 1.6J application. It includes a Type 1 plug and a 16ft charging cable for added convenience. Built to last, its durable construction withstands even the harshest weather conditions, ensuring maximum operational life. Control and monitor charging sessions remotely with WiFi connectivity. Experience efficient and hassle-free EV charging with this quality charger made in Canada.




Built in GFCI

208-240 VAC, 50-60Hz, Single Phase

Connect to any OCPP 1.6 Compatible Software

### FEATURES



- Delivers up to 10kW of power with adjustable current output
- Works seamlessly with any OCPP 1.6J application and includes a Type 1 plug and 16ft charging cable
- Durable construction withstands even the harshest weather conditions
- Control and monitor charging sessions remotely with WiFi connectivity
- Made in Canada



1-877-255-0004 | info@greenliteusa.com

[www.greenliteusa.com](http://www.greenliteusa.com)

V1-121224



## Electrification - SMART EV HOME CHARGING STATION

### PRODUCT SPECIFICATIONS

<b>Connectivity</b>	Ethernet (RJ-45) Wi-Fi, Compatible with OCPP 1.6J Applications
<b>EVSE Level</b>	AC Level 2
<b>Max Output Rating</b>	40A; 9.6 kW Maximum Output – For Use with 50A Circuit Rating
<b>Alternate Adjustable Output Ratings</b>	32A; 7.68 kW Maximum Output – For Use with 40A Circuit Rating
<b>Charger Cable Length</b>	16 ft
<b>Electrical Circuit / Input Power Requirements</b>	Circuit Requirement: Dedicated Single Phase 208-240VAC, 50/60 Hz.; Branch Breaker: Double Pole; Circuit Conductors: 3 wire - Line 1, Line 2 plus Ground
<b>Input Power Connection</b>	Standard: Plug-in, NEMA 14-50P with 11" cable
<b>Charging Station Color</b>	White front cover, grey back cover
<b>Installation Rating</b>	Type 4 rated for Indoor/Outdoor applications
<b>Operational Ratings</b>	Temperature: -40°F to 167°F (-40°C to 75°C); Humidity: up to 95%, Non-Condensing
<b>Mounting</b>	Wall or pole mounted
<b>Display &amp; Indicators</b>	4 LED Indicators-Power/Charging/Fault/Network
<b>Cable Management</b>	Easy Ev Plug with Cable Management™
<b>Standards and Compliance</b>	UL Certified, ENERGY STAR
<b>Dimensions</b>	EVSE: 12.20 x 8.66 x 3.74 inches
<b>Country of Origin</b>	Made in Canada

### MODEL INFORMATION

#### MODELS

GRS-6-24-P / GRS-14-24-P

1-877-255-0004 | [info@greenliteusa.com](mailto:info@greenliteusa.com)

[www.greenliteusa.com](http://www.greenliteusa.com)

V1-121224

