

## Weatherization and Insulation - QUICK CURE POLYURETHANE FOAM SEALANT

This multi-purpose foam sealant is a high-performance, single component, Class 1 rated fire retardant polyurethane foam. It is moisture cured and its expansion makes it ideal for larger size gaps and holes. Available in 12oz aerosol cans.



### PRODUCT SPECIFICATIONS

<b>Material</b>	Polyurethane foam
<b>Yield per Can</b>	12 oz - 400 linear feet
<b>Dry Time/ Tack Free</b>	< 30 minutes
<b>Cure Time</b>	4 hours
<b>Shelf Life</b>	18 months (unopened)
<b>Application Temp. Range</b>	60°F to 100°F (10°C ~ 38°C)
<b>Cutttable</b>	< 1 hours
<b>ICC-ES</b>	ESR-1926
<b>R-Value</b>	4 – 5 / in (25mm)
<b>Use</b>	Indoor/outdoor use
<b>Color</b>	Off-white
<b>Standards</b>	Meets ASTM E84/UL 723 ASTM E814 Class A Fire Rated UL Classified



### FEATURES

- High yield formula
- Weather-resistant bond seals out drafts and moisture
- Physically blocks insects and other pests
- Paintable / sandable
- Saves energy
- Straw and adapter included

### USES

Through-penetrations  
Gaps and cracks in foundations,  
Crawlspace, attics, and basements  
Partitions and stud walls  
Top and bottom of stair stringer  
Space connections in soffits and drop ceilings  
Concrete slabs  
Sill plates  
Rim joists

### MODEL INFORMATION

MODEL NUMBER	CASE QTY
WX/SPFM/QUICKCURE/1	12

1-877-255-0004 | [info@greenliteusa.com](mailto:info@greenliteusa.com)  
[www.greenliteusa.com](http://www.greenliteusa.com)

V1 - 20250123

